

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Cancel).
2. (Cancel).
3. (Cancel).
4. (Cancel).
5. (Cancel).
6. (Cancel).
7. (Cancel).
8. (Cancel).
9. (Cancel).
10. (Cancel).
11. (Cancel).
12. (Cancel).
13. (Cancel).
14. (Cancel).
15. (Previously presented) An apparatus for injecting dry powder, the apparatus comprising;

 a first end;

 an end opposite;

 an ejector located between the first end and the end opposite; and

a container comprising means of creating an aerosol of the dry aerosolized dry powder located between the ejector and the end opposite wherein the container is shaken vertically using a shaker comprises a vibrator, two or more vertical bars extending upwards from the vibrator, a horizontal bar in between the vertical bars, and a spring on one or more of the vertical bars, wherein the container is placed on top of the vibrator and in between the vertical bars, and the spring acts to shake the container vertically, and

wherein pressured gas is introduced through the first end, and the end opposite is bifurcated wherein one portion discharges the aerosolized powder and ~~the~~ other portion loops back and connects to the ejector.

16. (Original) The apparatus of claim 15, wherein the first end comprises a tube.

17. (Original) The apparatus of claim 16, wherein the tube is composed of a material selected from the group consisting of glass, plastic, ceramic, and metal.

18. (Original) The apparatus of claim 16, wherein ratio of diameter of the tube to the ejector is about 1.1 to about 4.

19. (Previously presented) The apparatus of claim 18, wherein the ratio is about 1.6 to about 2.5

20. (Previously presented) An apparatus for injecting dry powder comprising:

a container;

means for creating an aerosol of the dry powder within the container;

a conduit at the upper portion of the container having an inlet end and a discharge end, wherein the inlet end comprises an ejector and introduces a pressurized gas into the container and the discharge end is bifurcated wherein one portion connects to the ejector and ~~the~~ other portion discharges the aerosol of the powder; and

a shaker for shaking the container vertically, wherein the shaker comprises a vibrator, two or more vertical bars extending upwards from the vibrator, a horizontal bar in between the vertical bars, and a spring on one or more of the vertical bars, wherein the container is placed on top of the vibrator and in between the vertical bars.

21. (Previously presented) The apparatus of claim 20, wherein the pressurized gas is helium or argon.
22. (Previously presented) The apparatus of claim 20, wherein the ratio of diameter of the ejector to the inlet is about 0.25 to about 0.9.
23. (Previously presented) The apparatus of claim 22, wherein the ratio is about 0.4 to about 0.6.
24. (Previously presented) The apparatus of claim 20, wherein the dry powder comprises a metal catalyst supported on a powdered oxide substrate wherein the powdered oxide substrate has a particle size of 0.5 μm to 5 μm .
25. (Previously presented) The apparatus of claim 20, wherein the spring is located immediately below the horizontal bar.